

CHALLENGER BATTERY



EVG 12-150S (12V150Ah)





Specification

Cells Per Unit	6
Voltage Per Unit	12V
Capacity	150Ah@20hour-rate to 1.75V per cell @25°C
Weight	Approx. 41.0 Kg (Tolerance±5%)
Internal Resistance	≤4.0 mΩ (Full Charge Condition @25°C)
Terminal	Default F10(M8)
Max. Discharge Current	1500A (5 sec)
Cold Cranking Ampere(CCA)	715A
Max. Charging Current	45.0A
Reference Capacity	C3 112.5Ah
	C5 127.5Ah
	C10 143.0Ah
	C20 150.0Ah
Float Charging Voltage	13.6 V~13.8 V @ 25°C Temperature Compensation: -3mV/°C/Cell
Cycle Use Voltage	14.6 V~14.8 V @ 25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -20°C~60°C Charge: 0°C~50°C Storage: -20°C~60°C
Normal Operating Temperature Range	25°C±5°C
Self Discharge	Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C and then recharging is recommended. Monthly Self-discharge ratio is less than 3% at 25°C. Please charged batteries before using.
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.

EVG (Electric Vehicle) series is specially designed for frequent discharge deep cycle application. By using the specially designed active material, strong grids and thick plate construction, the EVG series battery offers reliable performance in high load situations and could provide competitive cycle performance. It is suitable for Electric Vehicle and Golf cart, Floor Machines, Forklifts, Aerial lifts, Robotics, Marine, RV, Mobility and Medical Equipment, and most outdoor application.



Dimensions



Length	327± 2mm (12.9 inches)
Width	180± 2mm (7.09 inches)
Height	271± 2mm (10.7 inches)
Total Height	276± 2mm (10.9 inches)
Terminal	Value
M5	6~7 N*m
M6	8~10 N*m
M8	10~12 N*m

Unit: mm

Constant Current Discharge Characteristics : A(25°C)

F.V/Time	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1. 60V	332.4	266.7	164.2	91.6	54.4	42.3	33.2	28.3	18.6	15.0	7.81
1. 65V	314.1	255.0	157.7	88.5	52.6	41.0	32.3	27.6	18.4	14.8	7.69
1. 70V	289.2	238.8	150.7	85.6	50.9	39.9	31.5	26.8	18.1	14.6	7.59
1. 75V	264.7	222.2	144.0	82.5	49.1	38.7	30.7	26.2	17.9	14.4	7.50
1. 80V	239.6	205.2	137.7	79.3	47.4	37.5	29.8	25.5	17.6	14.3	7.43
1. 85V	195.8	170.3	118.6	71.2	43.4	34.7	27.7	23.8	16.5	13.4	7.05

Constant Power Discharge Characteristics : WPC(25°C)









F.V/Time	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1. 60V	565.0	466.2	298.3	172.2	103.0	80.8	63.8	54.5	36.3	29.6	15.4
1. 65V	544.2	452.3	289.4	167.3	100.2	78.6	62.3	53.3	36.0	29.2	15.2
1. 70V	510.2	430.0	279.3	162.8	97.4	76.8	60.9	52.1	35.5	28.8	15.0
1. 75V	475.4	406.0	269.7	157.8	94.5	74.9	59.5	51.0	35.1	28.5	14.8
1. 80V	437.9	380.1	260.4	152.7	91.6	72.8	58.0	49.8	34.6	28.2	14.7
1. 85V	364.2	319.9	226.5	137.8	84.3	67.6	54.1	46.6	32.5	26.5	14.0

(Note) The above characteristics data are average values obtained within three charge/discharge cycle not the minimum values.

The battery must be fully charged before the capacity test. The C20 should reach 95% after the first cycle and 100% after the third cycle.

If F22 terminal is selected and the discharge current is more than 0.25C, the threaded terminal of terminal F22 shall not be used in connection, but the lead pole shall be connected.

CHALLENGER BATTERY



(Note) All above information shall be changed without prior notice, Accutrade reserves the right to explain and update the latest information.